



SATA 22PIN FEMALE

SATA 22PIN MALE

SATA 22PIN MALE

SATA 22PIN FEMALE

AFTER MOLDING

PIN ASSIGNMENT

CN:1	CN:2	CN:3	CN:4
1	1	8	8
2	2	9	9
3	3	10	10
4	4	11	11
5	5	12	12
6	6	13	13
7	7	14	14
		15	15
		16	16
		17	17
		18	18
		19	19
		20	20
		21	21
		22	22

PART NUMBER:  
**SASASA - 2 2 \* T - 4 4 1**

SERIES ——— NO. OF POS. ——— BAG PACKAGE ———  
 TIN PLATING ON SOLDER TAIL ———  
 CONTACT PLATED OPTION ———

1: GOLD FLASH  
 3: 3u" GOLD  
 5: 5u" GOLD  
 7: 15u" GOLD  
 9: 30u" GOLD

MATERIALS

HOUSING: LCP (UL 94V-0)  
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA  
 TIN PLATING ON SOLDER TAIL

SPECIFICATION

CURRENT RATING: 1.5 AMP MAX  
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE  
 CONTACT RESISTANCE: 30m OHMS MAX  
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V  
 OPERATION TEMPERATURE: -40°C~+85°C

 WWW.ZICONN.COM 886-3-4687695	TOLERANCES	REV.	A	DRAWN BY	Frank 2018/7/15	TITLE	ADAPTER, SATA 7+15 FEMALE TO SATA 7+15 MALE			
	X.±0.40 .XX±0.20 .X±0.30 .XXX±0.10		APPROVED BY	Lion 2018/7/15	DRAW NO.	SASASA-001	UNIT	MM	Sheet	1/1