



MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0)
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA
 TIN PLATING ON SOLDER TAIL

SPECIFICATION

CURRENT RATING: 0.5 AMP MAX
 DIELECTRIC WITHSTANDING: 300V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 20m OHMS MAX
 OPERATION TEMPERATURE: -40°C~+80°C

PART NUMBER:

BSSPP - 3 6 * T - 1 1 1

SERIES ——— NO. OF POS. ——— TIN PLATING ON SOLDER TAIL ——— TRAY PACKAGE

CONTACT PLATED OPTION

- 1: GOLD FLASH
- 3: 3u" GOLD
- 5: 5u" GOLD
- 6: 10u" GOLD
- 7: 15u" GOLD
- 9: 30u" GOLD



TOLERANCES	
X.±0.40	.XX±0.20
.X±0.30	.XXX±0.10

REV.	A	DRAWN BY	Zhong 2018/8/20	TITLE	MINI SAS HD 0.75mm PITCH, R/A, PRESS FIT TYPE				
		APPROVED BY	Lion 2018/8/20	DRAW NO.	BSSPP-001	UNIT	MM	Sheet	1/1