

**MATERIALS**

HOUSING: PBT (UL 94V-0)  
 SHELL: COPPER ALLOY OR SPCC, NICKEL PLATING  
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA  
 TIN PLATING ON SOLDER TAIL

**SPECIFICATION**

CURRENT RATING: 1 AMP MAX  
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE  
 CONTACT RESISTANCE: 30m OHMS MAX  
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V  
 OPERATION TEMPERATURE: -40°C~+85°C


**PART NUMBER:**

BUSAU - 0 4 \* T \* - 1 1 7 \*

SERIES — NO. OF POS. — CONTACT PLATED OPTION — TRAY PACKAGE — SHELL MATERIAL OPTION  
 HOUSING COLOR OPTION  
 BLANK: BLACK  
 W: WHITE  
 T: TIN PLATING ON SOLDER TAIL  
 1: GOLD FLASH  
 3: 3u" GOLD  
 5: 5u" GOLD  
 6: 10u" GOLD  
 7: 15u" GOLD  
 9: 30u" GOLD



TOLERANCES	
X.±0.40	.XX±0.20
.X±0.30	.XXX±0.10



REV. A  
 DRAWN BY Zhong 2018/9/7  
 APPROVED BY Lion 2018/9/7

TITLE	USB A TYPE, PCB MOUNT, UPRIGHT, METAL SHIELD, FEMALE			
DRAW NO.	BUSAU-007	UNIT	MM	Sheet
				1/1