



INFORMATION

P1: RF1, BLACK IN INSULATOR COLOR
 GOLD PLATING ON CONTACT AREA
 P2: RF1, BLACK IN INSULATOR COLOR
 GOLD PLATING ON CONTACT AREA
 TUBE: OD. 1.00, BLACK
 CABLE: OD. 1.13

SPECIFICATION

IMPEDANCE: 50 OHMS
 FREQUENCY RANGE: 0-6 GHz
 VSWR: 1.30 MAX AT 0-3 GHz
 1.50 MAX AT 3-6 GHz
 DIELECTRIC WITHSTANDING: 200V AC FOR ONE MINUTE
 INSULATION RESISTANCE: 500M OHM MIN
 CONTACT RESISTANCE:
 CENTER CONTACT -20 MILLI-OHMS MAX
 OUTER CONDUCTOR -20 MILLI-OHMS MAX

PART NUMBER:
 LPXPX - * 1 - 7 5 *
 SERIES ————
 CONTACT PLATED OPTION ————
 CABLE COLOR OPTION
 BLANK: BLACK
 G: GRAY
 W: WHITE

- 1: GOLD FLASH
- 3: 3u" GOLD
- 5: 5u" GOLD
- 6: 10u" GOLD
- 7: 15u" GOLD
- 9: 30u" GOLD

 WWW.ZICONN.COM 886-3-4687695	TOLERANCES	REV.	A	DRAWN BY	Zhong 2019/7/25	TITLE	MICRO COAXIAL (RF1) R/A FEMALE TO MICRO COAXIAL (RF1) R/A FEMALE, CABLE			
	X.±0.40 .XX±0.20 .X±0.30 .XXX±0.10		APPROVED BY	Lion 2019/7/25	DRAW NO.	LPXPX-005	UNIT	MM	Sheet	1/1