



P1: RP TNC

P2: MMCX

INFORMATION

P1: TNC, WHITE IN INSULATOR COLOR
 GOLD PLATING ON CONTACT AREA
 P2: MMCX, WHITE IN INSULATOR COLOR
 GOLD PLATING ON CONTACT AREA
 CABLE: RG178, BROWN
 HEAT SHRINK TUBE: THERMOPLASTIC, BLACK

PART NUMBER:

LMMTN - * 1 - 4 1

SERIES

CONTACT PLATED OPTION

- 1: GOLD FLASH
- 3: 3u" GOLD
- 5: 5u" GOLD
- 6: 10u" GOLD
- 7: 15u" GOLD
- 9: 30u" GOLD

SPECIFICATION

IMPEDANCE: 50 OHMS
 FREQUENCY RANGE: 0-6 GHz
 VSWR: 1.80 MAX



| TOLERANCES | |
|------------|-----------|
| X.±0.40 | .XX±0.20 |
| .X±0.30 | .XXX±0.10 |

| | | | | | | | | | |
|------|---|-------------|-----------------|----------|---|------|----|-------|-----|
| REV. | A | DRAWN BY | Zhong 2019/6/21 | TITLE | TNC VERTICAL FEMALE RP TO MMCX VERTICAL MALE, CABLE | | | | |
| | | APPROVED BY | Lion 2019/6/21 | DRAW NO. | LMMTN-001 | UNIT | MM | Sheet | 1/1 |