



### MATERIALS

HOUSING: THERMOPLASTIC (UL 94V-0)  
 SHELL: SPCC, NICKEL PLATING  
 BOARDLOCK: COPPER ALLOY, NICKEL PLATING  
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA  
 TIN PLATING ON SOLDER TAIL

### SPECIFICATION

CURRENT RATING: 5 AMP MAX  
 DIELECTRIC WITHSTANDING: 1000V AC FOR ONE MINUTE  
 CONTACT RESISTANCE: 30m OHMS MAX  
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V  
 OPERATION TEMPERATURE: -55°C~+105°C

#### PART NUMBER:

BDBKC - 0 9 \* T \* - 2 1 2 \*

SERIES  
 NO. OF POS.  
 CONTACT PLATED OPTION  
 1: GOLD FLASH  
 3: 3u" GOLD  
 5: 5u" GOLD  
 7: 15u" GOLD  
 9: 30u" GOLD  
 TIN PLATING ON SOLDER TAIL  
 HOUSING COLOR OPTION  
 BLANK: BLACK  
 B: BLUE  
 TRAY PACKAGE  
 RIVETED & SCREW OPTION  
 1: RIVETED & SCREW LOCK  
 2: RIVETED & W/O SCREW  
 3: RIVETED & ADD SCREW