



P1: ANTENNA

P2: RF1

INFORMATION

P1: FR-4, L=47.50x7.20mm T=0.4mm  
 P2: RF1, BLACK IN INSULATOR COLOR  
 GOLD PLATING ON CONTACT AREA  
 CABLE: OD 1.13, BLACK

PART NUMBER:

LPX - \* 1 - 1 5

SERIES

CONTACT PLATED OPTION

- 1: GOLD FLASH
- 3: 3u" GOLD
- 5: 5u" GOLD
- 6: 10u" GOLD
- 7: 15u" GOLD
- 9: 30u" GOLD

SPECIFICATION

NORMAL IMPEDANCE: 50Ω  
 FREQUENCY RANGE: 2.4G-2.5GHZ  
 RETURN LOSS: -10dBi MAX  
 VSWR: 2.0 MAX  
 PEAK GAIN: 4dBi

**ZICONN**  
 ELECTRONIC CO., LTD.  
 WWW.ZICONN.COM 886-3-4687695

TOLERANCES	
X.±0.40	.XX±0.20
.X±0.30	.XXX±0.10

REV.	A

DRAWN BY	Zhong 2020/1/20
APPROVED BY	Lion 2020/1/20

TITLE	2.4G ANTENNA, MICRO COAXIAL (RF1) R/A FEMALE, CABLE				
DRAW NO.	LPX-005	UNIT	MM	Sheet	1/1