



MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0), BLACK
 SHELL: COPPER ALLOY, NICKEL PLATING
 TERMINAL: COPPER ALLOY, GOLD PLATING

SPECIFICATION

CURRENT RATING: 1.8 AMP MAX (ONLY PIN 1, 5), OTHER 1 AMP MAX
 DIELECTRIC WITHSTANDING: 100V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 100M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -40°C~+105°C

PART NUMBER:
BUSTA - 0 5 * - 1 * E

SERIES ————
 NO. OF POS. ————
 CONTACT PLATED OPTION ————

1: 1u" GOLD
 3: 3u" GOLD
 5: 5u" GOLD
 7: 15u" GOLD
 9: 30u" GOLD

PACKAGE OPTION
 2: TAPE REEL
 3: TUBE

REV.	A	DRAWN BY	Frank 2021/3/29	TITLE	MICRO USB B TYPE, PCB MOUNT, SMT, METAL SHIELD, FEMALE				
		APPROVED BY	Lion 2021/3/29	DRAW NO.	BUSTA-014	UNIT	MM	Sheet	1/1