



MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0), BLACK
 LATCH: SUS, TIN PLATING
 TERMINAL: COPPER ALLOY, GOLD PLATED

SPECIFICATION

CURRENT RATING: 0.5 AMP MAX
 DIELECTRIC WITHSTANDING: 250V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 500M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -55°C~+85°C

PART NUMBER:

MMSLF - 1 2 4 * - 1 * 6

SERIES ————
 NO. OF POS. ————
 PACKAGE OPTION
 1: TRAY
 2: TAPE REEL

CONTACT PLATED OPTION

- 1: GOLD FLASH
- 2: 2u" GOLD
- 3: 3u" GOLD
- 5: 5u" GOLD
- 6: 10u" GOLD
- 7: 15u" GOLD
- 9: 30u" GOLD



| TOLERANCES | |
|------------|-----------|
| X.±0.40 | .XX±0.20 |
| .X±0.30 | .XXX±0.10 |

| | | | | | |
|------|---|-------------|------------------|----------|--|
| REV. | A | DRAWN BY | Zhong 2019/11/22 | TITLE | MINI PCI SOCKET 124 PIN, 0.80mm PITCH, PCB MOUNT, SMT, FEMALE WITH LATCH & POST (H=9.20mm) |
| | | APPROVED BY | Lion 2019/11/22 | DRAW NO. | MMSLF-006 |
| | | UNIT | MM | Sheet | 1/2 |

| | | | |
|------|----|-------|-----|
| UNIT | MM | Sheet | 1/2 |
|------|----|-------|-----|

