



PART NUMBER:
BUSTH - 0 5 * T - 2 * 5 *

SERIES ————
 NO. OF POS. ————
 CONTACT PLATED OPTION ————

1: GOLD FLASH
 3: 3u" GOLD
 5: 5u" GOLD
 7: 15u" GOLD
 9: 30u" GOLD

"X" LENGTH OPTION
 A: 0.85mm
 B: 1.60mm

PACKAGE OPTION
 1: TRAY
 3: TUBE
 4: BAG

TIN PLATING ON SOLDER TAIL

MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0), BLACK
 SHELL: STAINLESS STEEL, NICKEL PLATING
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA
 TIN PLATING ON SOLDER TAIL

SPECIFICATION

CURRENT RATING: 1.8 AMP MAX (ONLY PIN 1, 5), OTHER 1 AMP MAX
 DIELECTRIC WITHSTANDING: 100V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -25°C~+105°C