



INFORMATION

P1: SMA, WHITE IN INSULATOR COLOR, GOLD PLATED ON SHELL
 GOLD PLATING ON CONTACT AREA
 P2: RF4, BLACK IN INSULATOR COLOR, GOLD PLATED ON SHELL
 GOLD PLATING ON CONTACT AREA

CABLE: 1.13mm
 HEAT SHRINK TUBE: THERMOPLASTIC, BLACK
 NUT: COPPER ALLOY, GOLD PLATING
 WASHER: SUS, GOLD PLATING

SPECIFICATION

IMPEDANCE: 50 OHMS
 FREQUENCY RANGE: 0-6 GHz
 VSWR: 1.4:1 MAX DC-3 GHz
 1.65:1 MAX 3-6 GHz

PART NUMBER:

LPXSA - * * - 7 7

SERIES

CONTACT PLATED OPTION

"A" LENGTH OPTION

- 1: 141mm, CABLE GRAY
- 2: 163mm, CABLE RED
- 3: 223mm, CABLE BLACK
- 4: 296mm, CABLE WHITE

- 1: GOLD FLASH
- 3: 3u" GOLD
- 5: 5u" GOLD
- 6: 10u" GOLD
- 7: 15u" GOLD
- 9: 30u" GOLD