

P.C.B LAYOUT  
TOP VIEW ±0.05

**MATERIALS**

HOUSING: HI-TEMP. PLASTIC (UL 94V-0), BLACK  
SHELL: COPPER ALLOY, NICKEL PLATING  
TERMINAL: COPPER ALLOY, GOLD PLATING

**SPECIFICATION**

CURRENT RATING: 1.8 AMP MAX (ONLY PIN 1, 5), OTHER 1 AMP MAX  
DIELECTRIC WITHSTANDING: 100V AC FOR ONE MINUTE  
CONTACT RESISTANCE: 30m OHMS MAX  
INSULATION RESISTANCE: 100M OHMS MIN AT DC 500V  
OPERATION TEMPERATURE: -40°C~+105°C

**PART NUMBER:**

BUSTA - 0 5 \* - 1 2 C

SERIES

TAPE REEL PACKAGE

NO. OF POS.

CONTACT PLATED OPTION

- 1: GOLD FLASH
- 3: 3u" GOLD
- 5: 5u" GOLD
- 7: 15u" GOLD
- 9: 30u" GOLD



TOLERANCES	
X.±0.40	.XX±0.20
.X±0.30	.XXX±0.10

REV.


A

DRAWN BY

Zhong 2020/12/27

TITLE

MICRO USB B TYPE, PCB MOUNT, SMT, METAL SHIELD, FEMALE



APPROVED BY

Lion 2020/12/27

DRAW NO.

BUSTA-012

UNIT

MM

Sheet

1/1