



**MATERIALS**

HOUSING: PBT (UL 94V-0), BLUE  
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA  
 TIN PLATING ON SOLDER TAIL

**SPECIFICATION**

CURRENT RATING: 1 AMP MAX  
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE  
 CONTACT RESISTANCE: 30m OHMS MAX  
 INSULATION RESISTANCE: 5000M OHMS MIN AT DC 500V  
 OPERATION TEMPERATURE: -55°C~+105°C

**PART NUMBER:**

AFHBS - 2 1 0 \* T - 1 \* 1

SERIES ———  
 DUAL ROW ———  
 NO. OF POS. PER ROW ———  
 CONTACT PLATED OPTION ———  
 PACKAGE OPTION  
 1: TRAY  
 4: BAG  
 TIN PLATING ON SOLDER TAIL

**CONTACT PLATED OPTION**

- 1: GOLD FLASH
- 3: 3u" GOLD
- 5: 5u" GOLD
- 6: 10u" GOLD
- 7: 15u" GOLD
- 9: 30u" GOLD

B	MODIFY DRAW	2021.8.17
A	RELEASE	2018.1.25
REV.	DESCRIPTION	DATE

<b>ZICONN</b> ELECTRONIC CO., LTD. WWW.ZICONN.COM 886-3-4687695	TOLERANCES		REV.	B	DRAWN BY	Zhong 2018/1/25	TITLE	USB 3.0 20PIN, FEMALE HEADER 2.00mm PITCH, SOLDER TYPE			
	X.±0.40 .XX±0.20	.X±0.30 .XXX±0.10			APPROVED BY	Lion 2018/1/25	DRAW NO.	AFHBS-001	UNIT	MM	Sheet