



P.C.B. LAYOUT
TOP VIEW ±0.05

MATERIALS

HOUSING: THERMOPLASTIC (UL 94V-0)
SHELL: COPPER ALLOY, NICKEL PLATING
TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA
TIN PLATING ON SOLDER TAIL

SPECIFICATION

CURRENT RATING: 1.5 AMP MAX
DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
CONTACT RESISTANCE: 30m OHMS MAX
INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
OPERATION TEMPERATURE: -55°C~+85°C

PART NUMBER:

BUSBA - 0 4 * T - 1 1 1 *

SERIES — NO. OF POS. — CONTACT PLATED OPTION — HOUSING COLOR OPTION
BLANK: BLACK
W: WHITE
— TRAY PACKAGE — TIN PLATING ON SOLDER TAIL

- 1: GOLD FLASH
- 3: 3u" GOLD
- 5: 5u" GOLD
- 6: 10u" GOLD
- 9: 30u" GOLD

B	MODIFY PLASTIC	2023.5.9
A	RELEASE	2021.5.13
REV.	DESCRIPTION	DATE



TOLERANCES

X.±0.40	.XX±0.20
.X±0.30	.XXX±0.10

REV.	B	DRAWN BY	Zhong 2021/5/13	TITLE	USB B TYPE, PCB MOUNT, VERTICAL, METAL SHIELD, FEMALE				
		APPROVED BY	Lion 2021/5/13	DRAW NO.	BUSBA-001	UNIT	MM	Sheet	1/1