



P.C.B. LAYOUT
TOP VIEW ±0.05

MATERIALS

HOUSING: PBT (UL 94V-0), BLACK
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA
 TIN PLATING ON SOLDER TAIL

SPECIFICATION

CURRENT RATING: 0.5 AMP MAX
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -55°C~+85°C

PART NUMBER:

BSCAC - 2 6 8 * T - 1 1 1

SERIES ———
 PCB LAYOUT STYLE 2 ———
 NO. OF POS. ———
 CONTACT PLATED OPTION ———

TRAY PACKAGE
 TIN PLATING ON SOLDER TAIL

- 1: GOLD FLASH
- 3: 3u" GOLD
- 5: 5u" GOLD
- 6: 10u" GOLD
- 7: 15u" GOLD
- 9: 30u" GOLD

B	MODIFY DIMENSION	2022.8.16
A	RELEASE	2019.9.25
REV.	DESCRIPTION	DATE



TOLERANCES
X.±0.40 .XX±0.20
.X±0.30 .XXX±0.10

REV.	A	DRAWN BY	Zhong 2019/9/25	TITLE	SCSI, 1.27mm PITCH, PCB MOUNT, VERTICAL, 68PIN, FEMALE				
		APPROVED BY	Lion 2019/9/25	DRAW NO.	BSCAC-001	UNIT	MM	Sheet	1/1