



$$A = (\text{NUMBER OF POS. PER ROW}) \times 2.00 + 2.65$$

$$B = (\text{NUMBER OF POS. PER ROW}) \times 2.00 + 1.00$$

$$C = (\text{NUMBER OF POS. PER ROW}) \times 2.00 + 0.85$$

$$D = (\text{NUMBER OF POS. PER ROW} - 1) \times 2.00$$

**MATERIALS**

HOUSING: HI-TEMP. PLASTIC (UL 94V-0)  
 TERMINAL: COPPER ALLOY, GOLD PLATED

**SPECIFICATION**

CURRENT RATING: 2 AMP MAX  
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE  
 INSULATION RESISTANCE: 5000M OHMS MIN AT DC 500V  
 OPERATION TEMPERATURE: -40°C~+105°C

**PART NUMBER:**

ABHBE - 2 \* \* \* - 2 \* 1

- SERIES
- DUAL ROWS
- NO. OF POS. PER ROW (02 ~ 25 POS.)
- PACKAGE OPTION
  - 1: TRAY
  - 3: TUBE
  - 4: BAG
- CONTACT PLATED OPTION
  - 1: GOLD FLASH
  - 3: 3u" GOLD
  - 5: 5u" GOLD
  - 6: 10u" GOLD
  - 7: 15u" GOLD
  - 9: 30u" GOLD



TOLERANCES	
X.±0.40	.XX±0.20
.X±0.30	.XXX±0.10

REV.	A	DRAWN BY	Kiki 2022/11/10	TITLE	BOX HEADER, 2.00mm PITCH, PCB MOUNT, R/A, DUAL ROWS				
		APPROVED BY	Lion 2022/11/10	DRAW NO.	ABHBE-001	UNIT	MM	Sheet	1/1