


PART NUMBER:
ABLPT - 0 7 * T - 2 3 3

SERIES ——— NO. OF POS. ——— CONTACT PLATED OPTION ———

TUBE PACKAGE ——— TIN PLATING ON SOLDER TAIL ———

- 1: GOLD FLASH
- 3: 3u" GOLD
- 5: 5u" GOLD
- 6: 10u" GOLD
- 7: 15u" GOLD
- 9: 30u" GOLD



MATERIALS

HOUSING: LCP (UL 94V-0), BLACK
 FORK: COPPER ALLOY, TIN PLATING
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA
 TIN PLATING ON SOLDER TAIL

SPECIFICATION

CURRENT RATING: 7 AMP MAX
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 500M OHMS MIN AT DC 100V
 OPERATION TEMPERATURE: -40°C~+85°C



TOLERANCES	
X.±0.40	.XX±0.20
.X±0.30	.XXX±0.10

REV.	A	DRAWN BY	Kiki 2023/8/31
		APPROVED BY	Lion 2023/8/31

TITLE	LAPTOP BATTERY, 2.00mm PITCH, PCB MOUNT, ALL PLASTIC R/A 7PIN WITH FORK, MALE				
DRAW NO.	ABLPT-003	UNIT	MM	Sheet	1/1