



MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0), BLACK
 SHELL: COPPER ALLOY, NICKEL PLATING
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA
 TIN PLATED ON SOLDER TAIL

SPECIFICATION

USB
 CURRENT RATING: 1 AMP MAX
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 50m OHMS MAX
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -40°C~+85°C

RJ45
 CURRENT RATING: 1.5 AMP MAX
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 50m OHMS MAX
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -40°C~+85°C

LED ELECTRICAL CHARACTERISTIC				
Standard LED	Wavelength	Forward V (Min/Max)	Forward A	Type
				Green
Yellow	585nm	1.8v/2.8v	20mA	squareness

PART NUMBER:

SCMJUS - 1 6 * T - 7 1 4

SERIES NO. OF POS. TIN PLATING ON SOLDER TAIL TRAY PACKAGE

CONTACT PLATED OPTION

- 1: GOLD FLASH
- 3: 3u" GOLD
- 5: 5u" GOLD
- 7: 15u" GOLD
- 9: 30u" GOLD
- 11: 6u" GOLD



TOLERANCES
 X.±0.40 .XX±0.20
 .X±0.30 .XXX±0.10

REV. A DRAWN BY Zhong 2019/4/26 TITLE
 APPROVED BY Lion 2019/4/26 DRAW NO.

STACKED RJ45 + USB 2.0, PCB MOUNT, R/A, METAL SHIELD WITH LED
 SCMJUS-004 UNIT MM Sheet 1/1